

## Security locks

### Execution

Vibration-proof. When opening or closing the lock, press the key so that the bolt is lifted over the slot in the enclosure. The bolt engages automatically at the end of the 90° turn.

The hole pattern is the same for all locks, so they can be changed any time.

### Scope of supply

#### Brass + zinc die-cast variant:

- Steel bolt (L = 40 mm), mounted
- Steel Counter nut, galvanised

#### Stainless steel variant:

- V2A bolt (L = 45 mm), mounted
- V2A counter nut



1



2



3



4



5

Actuation	Material	Art. No.	Price [€]
<b>1 Double bit with cover</b> (standard locking system at ROWEKO. Key can only be removed when locked.)	Brass	<b>411 90 300</b>	
	Stainless steel (V2A)	<b>411 90 305</b>	
<b>2 S-rotary two way bolts with offset latch</b> (for all platform boxes and storage boxes from year of manufacture 04/2013 with Ø 65 mm) lock cover)	Brass	<b>411 90 304</b>	
<b>3 Lever</b> , for tube container only	Zinc die-cast, chrome-plated+ polyamide	<b>411 90 390</b>	
<b>4 Square</b> , outside, 8 mm	Zinc die-cast, chrome-plated	<b>411 90 320</b>	
<b>5 Triangular</b> , outside, 8 mm	Zinc die-cast, chrome-plated	<b>411 90 330</b>	

Other designs on request.

- 1 Double bit with cover (standard), Size H = 20 mm
- 2 Double bit with cover (offset latch), Size H = 6 mm
- 3 Lever, only suitable for tube container
- 4 Square, outside, 8 mm
- 5 Triangular, outside, 8 mm

