



Compact hose tube container, triple

Material

HD-PE black

Execution

End piece and flange are each attached to the tube container with 9 VA rivets. The flange is riveted from inside to outside. The cover is riveted with two VA hinges to the flange. The cover is locked standard with a double-bit security rotary bolt. The locking latches grasp behind the aluminum locking bracket.

Scope of delivery

Tube complete with assembled/riveted lid (cover with flange) and end-fitting.
1 two-way key.

Accessories / Options

- Other locking systems (p. 96)
- Door with flange on both sides
- Intermediate lengths are possible for all models (4% surcharge)

A-Ø x wall [mm]	Weight [kg/m]	Length [m]	Art. No.	Price [€]
160 x 3.9	5.85	2.4	121 24 300	
		3.0	121 30 300	
		5.0	121 50 300	
		6.0	121 60 300	
		7.0	121 70 300	
		8.0	121 80 300	
		10.0	121 99 300	
200 x 4.9	9.15	2.4	124 24 300	
		3.0	124 30 300	
		5.0	124 50 300	
		6.0	124 60 300	
		7.0	124 70 300	
		8.0	124 80 300	
		10.0	124 99 300	
Intermediate lengths			125 99 901	+ 4 %



1

2

Compact hose tube container, triple

1 Clip

Material

Stainless steel 1.4301, HD-PE black

Execution

3-piece, comprising:

- Tube bracket with clip (50 x 3 mm)
- Base plate with tube contour and bores
- with M8 x 40 galvanised screws (DIN 603), U washer and lock nut

Fixing advice

Max. distance between clips 1500 mm
e.g. 5000 mm tube = at least 4 clips

2 Door with flange and end cap

Material

HD-PE black

Execution

Fully mounted door with flange incl. security lock (double bit) and 1 key.
End cap separate.

Other locking systems (p. 96)

Accessories

Article for Ø [mm]	Weight [kg]	Art. No.	Price [€]
Clip			
160	1.45	421 00 001	
200	1.65	424 00 001	

Spare parts

Article for Ø [mm]	Weight [kg]	Size [mm]	Art. No.	Price [€]
Door with flange				
160	0.97	350 x 330 x 35	421 00 302	
200	1.28	430 x 415 x 40	424 00 302	
End cap				
160	0.40		421 00 005	
200	0.48		424 00 005	
HD-PE tube black, without attachments				
40-1000			On request	