



1

Hose tube container, single for silo vehicles

Material

HD-PE black

Execution

End-fitting and flange are fastened with 4 ea. VA rivets to the tube. The flange is riveted from inside to outside (exception: 125 mm). The cover is riveted with a VA hinge to the flange. The cover is locked as standard with a double-bit security rotary bolt. The locking latch grasps behind the aluminum locking bracket.

Scope of delivery

Tube complete with mounted/riveted lid (cover with flange) and end-fitting.
1 two-way key.

Accessories / Options

- Tube support
- Other locking systems (p. 96)
- Door with flange on both sides
- Intermediate lengths are possible for all models (4% surcharge)

1 Cover for Ø 250 mm with rounded corners

A-Ø x wall [mm]	Weight [kg/m]	Length [m]	Art. No.	Price [€]
125 x 3.1	1.23	2.4	106 24 300	
		5.0	106 50 300	
		6.0	106 60 300	
		7.0	106 70 300	
160 x 3.9	1.95	2.4	101 24 300	
		3.0	101 30 300	
		5.0	101 50 300	
		6.0	101 60 300	
		7.0	101 70 300	
		8.0	101 80 300	
180 x 4.4	2.48	10.0	101 99 300	
		2.4	102 24 300	
		3.0	102 30 300	
		5.0	102 50 300	
		6.0	102 60 300	
200 x 4.9	3.05	7.0	102 70 300	
		10.0	102 99 300	
		2.4	103 24 300	
		3.0	103 30 300	
		5.0	103 50 300	
		6.0	103 60 300	
250 x 6.2	4.83	7.0	103 70 300	
		8.0	103 80 300	
		10.0	103 99 300	
		2.4	104 24 300	
		5.0	104 50 300	
Intermediate lengths		6.0	104 60 300	
		7.0	104 70 300	
			125 99 901	+ 4 %

Hose tube container, single for silo vehicles

1 Clip

3-piece, comprising a stainless steel 1.4301 U bracket (50 x 3 mm), black HD-PE end cap, incl. M10 screw (DIN 603), lock nut and U washer

Accessories

Article for Ø [mm]	Weight [kg]	Art. No.	Price [€]
Clip			
160	0.72	401 00 001	
180	0.80	402 00 001	
200	0.88	403 00 001	
250	1.10	404 00 001	
VA screws for mounting on vehicle (set)			
M8 x 20 (2 units)	0.04	409 00 002	



Instructions for applying clip



1

2 Chassis bracket – flat

2-piece, comprising a stainless steel 1.4301 tube bracket with clip (35 x 3 mm), black HD-PE base plate with tube contour and bores, without screws

Accessories

Article for Ø [mm]	Weight [kg]	Art. No.	Price [€]
Chassis bracket flat			
160	0.45	401 00 535	



2

3 Chassis bracket – round

2-piece, comprising an M10 stainless steel A2 tube bracket with 65 mm thread, incl. lock nut and U washer, black HD-PE base plate with tube contour and bores

Accessories

Article for Ø [mm]	Weight [kg]	Art. No.	Price [€]
Chassis bracket round			
125	0.36	406 00 575	
160	0.72	401 00 575	
180	0.80	402 00 575	
200	0.88	403 00 575	
250	1.10	404 00 575	



3

Fixing advice

Max. distance between clips 1500 mm
e.g. 5000 mm tube = at least 4 clips

4 Cover and end-fitting

Cover with flange (HD-PE) black, completely mounted incl. security rotary bolt and 1 key (standard: two-way), end-fitting separate.

Other locking facilities (p. 96)

Spare parts

Article for Ø [mm]	Weight [kg]	Size [mm]	Art. No.	Price [€]
Door with flange				
125	0.33	150 x 150 x 35	406 00 302	
160	0.52	185 x 185 x 35	401 00 302	
180	0.58	205 x 205 x 35	402 00 302	
200	0.60	225 x 225 x 35	403 00 302	
250	0.88	290 x 295 x 35	404 00 302	
End cap				
125	0.06		406 00 005	
160	0.12		401 00 005	
180	0.16		402 00 005	
200	0.17		403 00 005	
250	0.26		404 00 005	
HD-PE tube black, without attachments				
40-1000			On request	



4