



Pneumatic spring

The reliable way of transporting tools on platform trucks. The light tare weight of just 33.7 kg (incl. handles) means that the box is easy to transport and can be comfortably packed and unpacked in the workshop or on the construction site. Tool transportation: clean, practical, theft-proof!

### Good ideas for simple handling

- Box can be placed close to the driver's cabin to avoid an unnecessary reduction of the cargo area. The 45° cover opening angle means that the box can be opened wide.
- Rear view is not inhibited
- Gas pressure springs hold the cover open

### Available as an accessory

- Anti-skid mount on the platform
- Handles for transportation

### Approved ROWEKO quality

- Light and robust construction from HD-PE
- Impact-resistant, even in extreme temperatures
- Splash-water-resistant and weatherproof
- Chemical and UV-resistant
- Hinges and rivets made from VA steel
- Safe and secure: Snap lock





## Platform toolbox

### Size (width x depth x height)

1750 x 800 x 720 mm

### Material

HD-PE black

### Weight

32.50 kg

### Execution

The lid (snap lock) is riveted to the box with 7 hinges. 2 gas pressure springs make it easy to open the lid and keep it open. For additional reinforcement, angles are riveted to the front (with cover) and sides. The hinges and rivets are made from stainless steel (V2A) and the angles are made from aluminium.

### Locking system as per description on page 31

Article	Art. No.	Price [€]
<b>Snap lock</b>		
With locking split pin	<b>221 60 000</b>	
With padlock (simultaneous locking)	<b>221 60 600</b>	

### Accessories

Article	Weight [kg]	Art. No.	Price [€]
<b>Assembled handles</b>	1.20	<b>221 60 001</b>	
4 pieces max. weight of 35 kg each			
<b>Mounting profiles</b>	1.90	<b>421 20 030</b>	
- 2 x clamp plates (540 x 96 x 10 mm)			
- Screw set for box installation			

- 1 Mounting profiles
- 2 Handles



Installation instructions for platform crate